Application No.: 10/019,134

IN THE CLAIMS

Please delete Claims 2 and 11.

Please amend Claims 1, 3 – 10, and 12 – 16 to read as follows:

- 1. UV illuminating device for crosslinking biocompatible, polymerisable material in order to produce an ophthalmic moulding in a casting mould consisting of two mould halves, comprising at least one UV lamp which is surrounded by a plurality of optical fibres, wherein each optical fibre is linked to one casting mould.
- 3. UV illuminating device according to claim 1, wherein the UV lamp is a mercury lamp.
- **4.** UV illuminating device according to claim 3, wherein the UV lamp is a doped mercury lamp.
- **5.** UV illuminating device according to Claim 1, wherein the optical fibres are liquid optical fibres.
- **6.** UV illuminating device according to Claim 1, wherein the emission spectrum of the UV lamp has a high UV intensity at 280 360 nm.
- 7. UV illuminating device according to Claim 1, further comprising a sensor, wherein the sensor measures the radiation intensity of the UV lamp and is connected to a regulating unit to regulate the UV radiation.
- **8.** UV illuminating device according to Claim 1, further comprising a measuring unit which measures the emitting UV radiation intensity.
- **9.** UV illuminating device according to one or more of claims 1 to 8, whereby, wherein in order to couple in the UV radiation, a quartz rod is respectively provided between the UV lamp and the light admission area of each of the optical fibres.
- **10.** UV illuminating device according to claim 9, wherein a cut-on filter is provided between the quartz rod and the optical fibre in order to absorb short-waved UV radiation.
- 12. UV illuminating device according to Claim 1, wherein a diaphragm is provided between the optical fibre and the UV lamp.
- **13.** UV illuminating device according to claim 12, wherein the aperture of the diaphragm is adjusted by means of a stepping motor unit.

Application No.: 10/019,134

14. UV illumination device according to Claim 1, wherein the aperture of the diaphragm is controlled in accordance with the measurement of UV radiation intensity being emitted.

- **15.** UV illuminating device according to Claim 1, wherein a UV condenser is mounted between the optical fibre and the upper mould half.
- **16.** UV illuminating device according to Claim 1, wherein the optical fibres are arranged radially around the UV lamp in relation to the longitudinal axis of the UV lamp.

BEST AVAILABLE COPY